



## SAW BANDPASS FILTER

**PART NO.: ACTFH021-0773SA-1109**

<b>Product Type:</b>	<b>Customer:</b>
SAW filter for LTE BAND 28_A (Rx ).	
	<b>Customer Part NO.:</b>
	<b>Issued Date:</b>


## Features

SAW filter for LTE BAND 28\_A (Rx ).

- 1 High stability and reliability with good performance and no adjustment.
- 2 Single ended to Single ended.
- 3 Narrow and sharp pass band characteristics. RoHS compatible.
- 4 Low insertion loss and deep stop band attenuation for interference.
- 5 Useable Pass band 29.5MHz.
- 6 Package size 1.1mm\*0.9mm.

## Package Dimensions


Ceramic Package: Unit: mm



## Pin Configuration

1	Input
4	Output
2,3,5	Ground

## Marking



Top View, Laser Marking

"aC" Part number

"." Dot marking, indicates input 1

" 1" Terminal1

The first "\*": Month Code (The code shown below varies in a 4-year-cycle)

Month	1	2	3	4	5	6	7	8	9	10	11	12
2016/2020	n	p	q	r	s	t	u	v	w	x	y	z
2017/2021	A	B	C	D	E	F	G	H	J	K	L	M
2018/2022	N	P	Q	R	S	T	U	V	W	X	Y	Z
2019/2023	a	b	c	d	e	f	g	h	i	j	k	m

The second "\*": Date Code

<b>data</b>	□1st	□2nd	3rd	4th	5th	6th	7th	8th	9th	10th	
<b>code</b>	A	B	C	D	E	F	G	H	J	K	
<b>data</b>	11th	12th	13th	14th	15th	16th	17th	18th	19th	20th	
<b>code</b>	L	M	N	P	Q	R	S	T	U	V	
<b>data</b>	21st	22nd	23rd	24th	25th	26th	27th	28th	29th	30th	31st
<b>code</b>	W	X	Y	Z	a	b	d	e	f	g	h

## Maximum Ratings

DC Voltage (between any Terminals)	$V_{DC}$	10	V
RF Power (in BW)	$P$	15 dBm /2000hr@55°C	
Operating Temperature Range	$T_A$	-30 ~ +85	°C
Storage Temperature Range	$T_{stg}$	-40 ~ +85	°C
ESD Voltage (HB)	$V_{ESD}$	>150	V
Moisture Sensitivity Levels	$MSL$	2A	

## Electrical Characteristics:


Terminating impedance:  $Z=50\ \Omega$

Center Frequency	$f_C$	—	773	—	MHz	
Insertion-loss	@758.25—787.75MHz	$IL$	—	2.4	3.0	dB
	@760.5—785.5MHz		—	2.0	2.5	
Pass band Ripple @758.25—787.75MHz	$Pr$	—	1.0	1.5	dB	
Rejection	DC-703MHz	50	58	--	dB	
	703-748MHz	40	46	--		
	814-824MHz	42	47	--		
	824-915MHz	45	50	--		
	915-1500MHz	40	45	--		
	1500-2500MHz	33	38	--		
	2500-6000MHz	25	30	--		
VSWR @758.25—787.75MHz	—	—	1.7	2.1		

 RoHS Compliant


 Electrostatic Sensitive Device

## Test Circuit




## Typical Frequency Response


S21



S11 S22



Far side




### Stability Characteristics

Item No.	Test Item	STD Reference	Test Conditions	per lot
	Preconditioning	JESD22-A113	1) Temperature Cycling, 5 cycles -40°C to 85°C; 2) Bake, 24 hrs @85±5°C; 3)Moisture Soak, Soak time and conditions per IPC/JEDEC J-STD-020 based on device MSL level; 4) Reflow, 3 reflow cycles; 5) Drying, Room ambient temperature.	All behind
1	Temperature Cycling	JESD22-A104	-40°C / +85°C,5°C/min,15min dwell,<1 min transfer time,500cycles	3*25 pcs
2	High Temperature Storage	JESD22-A103	Temperature=85°C, 1000 hours.	3*25 pcs
3	Temperature Humidity no bias	JEDEC Std A101-B	85°C 85%RH 240 hours	3*25 pcs
4	Human Body Mode ESD	JESD22-A114	Ta=25°C, ≥100V	3 pcs
5	Charge Device Mode ESD	JESD22-C101	Ta=25°C, ≥100V	3 pcs
6	Solderability	JESD22-B102	Wetting: 245°C, 5s.	22 pcs
7	Drop Test	JESD22-B111	1500 Gs, 0.5 millisecond duration, half-sine pulse.	20 pcs
8	Mechanical Shock	JESD-47	Shock pulse of 1500g with pulse duration of 0.5+/-0.1msec (X ,Y & Z); 5 shocks per axis.	3*25 pcs


**Requirements:** The SAW filer shall remain within the electrical specifications after tests.

### Packing Information

#### Carrier Tape



#### Reel Dimensions



## Outer Packing

Carton Box I	100000	240×210×285	anti-static plastic bag & carton box 1 reel / bag 10bags / box (100000 pcs) 30 bags / box (300000pcs)	2.15
Carton Box II	300000	470×310×285		6.22


Unit: mm

Unit: kg

### Remarks

- SAW devices should not be used in any type of fluid such as water, oil, organic solvent, etc.
- Be certain not to apply voltage exceeding the rated voltage of components.
- Do not operate outside the recommended operating temperature range of components.
- Sudden change of temperature shall be avoided, deterioration of the characteristics can occur.
- Be careful of soldering temperature and duration of components when soldering.
- Do not place soldering iron on the body of components.
- Be careful not to subject the terminals or leads of components to excessive force.
- SAW devices are electrostatic sensitive. Please avoid static voltage during operation and storage.
- Ultrasonic cleaning shall be avoided. Ultrasonic vibration may cause destruction of components.

### Recommended Soldering Profile



© ACT 2018. All Rights Reserved.

1. The specifications of this device are subject to change or obsolescence without notice.
2. Typically, equipment utilizing this device requires emissions testing and government approval, which is the responsibility of the equipment manufacturer.
3. Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.