


WX16S Series

1.6 x 1.0mm Watch crystal




RoHS & REACH compliant
Vacuum sealed miniature ceramic package for excellent stability
Low power consumption
Suitable for UAVs and Drones




Parameters		Specification	Remarks
Frequency	F_nom	32.768kHz	
Frequency tolerance	F_tol	±20ppm	At 25°C ± 3°C
Operating temperature range	T_use	-40°C ~ +85°C	
Storage temperature	T_stg	-55°C ~ +125°C	
Temperature coefficient	K	-0.036±10% ppm/Δ°C²	
Turnover temperature	Ti	25°C ± 5°C	
Load capacitance	CL	7pF, 9pF, 12.5pF	Other load capacitances are available - please contact ACT
Equivalent series resistance	ESR	90KΩ max	Other lower ESR options are available - please contact ACT
Shunt capacitance	C0	2.0pF max	
Drive level	DL	0.1μW typical, 1.0μW max	
Frequency aging	F_age	±3.0ppm max	At 25°C, First year
Insulation resistance	IR	500MΩ min	At DC100V ± 15V

Dimensions (mm)



Frequency stability vs temperature



Part number generation

WXS	00003	G	I	H	D	-PF
ACT Series Code	Frequency (KHz)	Frequency Tolerance (±ppm)	Operating Temperature Range (°C)	Load capacitance (CL)	Packaging (Tape & Reel)	RoHS
WXS	32.768kHz = 00003	±20 = G	-40 ~ +85 = I	7.0pF = M 9.0pF = K 12.5pF = H	Loose/Sample = L 5000pcs = H	RoHS = -pF


Note: It is important to suffix the above part number with full frequency required to give a completed part number as illustrated below.
Full Example Part Number : **WXS00003GIHD-PF (32.768kHz)**

WX16S Series

1.6 x 1.0mm Watch crystal



Reflow profile



Additional information

Drawing control: (Internal use only)
Commodity code: 854 160 00 00
Issue number: N2
Date: 15/03/2023
Internal reference: H2

ACT (A wholly owned Acal BFi Company)
+44 (0) 118 978 8878 | sales@act.co.uk | www.act.co.uk
ISO9001 Registered
Specifications subject to change without notification